

# 12V Single



## ▼ Photometrics

12V 15"	FC	138	38	16	9	6	4
	Feet	1	2	3	4	5	6
12V 2ft	FC	186	57	27	15	10	7
	Feet	1	2	3	4	5	6
12V 4ft	FC	212	89	46	28	19	13
	Feet	1	2	3	4	5	6

12V 15"	LUX	1992	581	259	145	92	65
	Meters	0.25	0.5	.75	1	1.25	1.5
12V 2ft	LUX	2605	883	412	236	153	109
	Meters	0.25	0.5	.75	1	1.25	1.5
12V 4ft	LUX	2278	1217	700	432	289	211
	Meters	0.25	0.5	.75	1	1.25	1.5

## ▼ Fixture Specifications

Fixture	Lamp	Lamp Type	Dimensions	Weight w/ Lamp
15" Fixture/12V	1	F30/T12	17.5 x 3.5 x 3" (44.5 x 9 x 7.5cm)	1.0 lb (0.5kg)

## ▼ Ballast Specifications

Ballast	Input Voltage	Output Frequency	Dimming	Lamp	Amperage	Dimensions	Weight
12V Single	12VDC	25 kHz	100%-15%	1	F75/4.6A, F40/2.8A F30/1.9A	7 x 6.5 x 2.5" (18 x 16.5 x 6.5cm)	2.2 lb (1.0kg)

## ▼ Details



The 12V Single puts a compact, controllable, portable dimming system in the palm of your hand. This small cool light location unit takes center stage when it comes to lighting cramped interiors such as a bus, car, elevator or any place on a set that can't be reached via an external light source. Like all Kino Flos, it is a low energy, low profile and low maintenance workhorse for film and video lighting professionals.

- 12V Dimming Ballast
- Flicker-free, instant-on
- Runs lamps 15" to 4ft
- Removable Lamp Harness
- Focusing Louver
- True Match® daylight and tungsten lamps

## ▼ 12V Single Kit



**KIT-140X**  
12V Single Kit, 12VDC

Contents	Dimensions
2 12V Single Ballast XLR	21 x 7.5 x 17"
2 15" 12V Single Fixture	(53.5 x 19 x 43cm)
2 Extension, 25ft	<b>Weight</b>
1 Car Adapter XLR	14 lb (6.3kg)
1 Alligator Clip Adapter XLR	
1 Splitter XLR	
1 Travel Case	

## ▼ 12V Kit Components



**CFX-15V**  
15" Fixture/12V



**X04-25**  
Extension, 25ft



**BAL-140X**  
12V Single Ballast XLR,  
12VDC



**PWCAX**  
DC Alligator Adapter XLR,  
12ft



**PWC-CX**  
DC Car Adapter XLR, 6ft



**PWC-X42**  
Splitter XLR



**KAS-12V**  
12V Single Travel Case

## ▼ 12V Accessories/ Lamps



**HAR-4801**  
4ft Single Harness  
**HAR-2401**  
2ft Single Harness



**PWS-156X**  
Power Supply 6.6A,  
100-250VAC/12VDC  
4-Pin XLR



**X04-A16**  
Single to 4Bank Combiner  
**X04-A9**  
Single to Double Combiner



**152-K32-S**  
15" Kino KF32  
**152-K55-S**  
15" Kino KF55