



**KINO FLO**<sup>®</sup>  
Lighting Systems



# **BarFly**

Lighter & Brighter  
For close-ups and tight locations



## ▼ BarFly 200 Kits



**KIT-B22-G120**  
BarFly 200 Kit, 120VAC (2-Unit)

**KIT-B22-G230**  
BarFly 200 Kit, 230VAC (2-Unit)

**Includes:** BarFly 200 Fixture (2), BarFly 200 Ballast (2), Mount (2), BarFly Louver 60° (2), BarFly Louver / Gel Bag (2), Lamp Case (1), Ship Case (1)

**Dimensions**      **Weight**  
31 x 19.5 x 10.5"      43 lb  
(77.5 x 49 x 26.5 cm)      (19.4kg)



**KIT-B200-G120**  
BarFly 200 Kit, 120VAC (1-Unit)

**KIT-B200-G230**  
BarFly 200 Kit, 230VAC (1-Unit)

**Includes:** BarFly 200 Fixture (1), BarFly 200 Ballast (1), Mount (1), BarFly Louver 60° (1), BarFly Louver / Gel Bag (1), Soft Bag (1)

**Dimensions**      **Weight**  
19.5 x 9 x 13.5"      16.6 lb  
(49.5 x 22.8 x 33 cm)      (7.5kg)

## ▼ BarFly 200 System



**BAR-200G**  
BarFly 200 Fixture w/ Gel Frame and Louver 90°



**MTP-B41S**  
Mount w / Baby Short (16mm)



**BAL-207-G120**  
BarFly 200 Ballast, 120VAC

**BAL-207-G230**  
BarFly 200 Ballast, 230VAC

## ▼ BarFly 100 Kits



**KIT-B12-G120**  
BarFly 100 Kit, 120VAC (2-Unit)

**KIT-B12-G230**  
BarFly 100 Kit, 230VAC (2-Unit)

**Includes:** BarFly 100 Fixture (2), BarFly 100 Ballast (2), Mount (2), BarFly Louver 60° (2), BarFly Louver / Gel Bag (2), Lamp Case (1), Ship Case (1)

**Dimensions**      **Weight**  
27.5 x 19.5 x 10.5"      35 lb  
(69 x 49 x 26.5 cm)      (15.8kg)



**KIT-B100-G120**  
BarFly 100 Kit, 120VAC (1-Unit)

**KIT-B100-G230**  
BarFly 100 Kit, 230VAC (1-Unit)

**Includes:** BarFly 100 Fixture (1), BarFly 100 Ballast (1), Mount (1), BarFly Louver 60° (1), BarFly Louver / Gel Bag (1), Soft Bag (1)

**Dimensions**      **Weight**  
19.5 x 9 x 13.5"      12.8 lb  
(49.5 x 22.8 x 33 cm)      (5.8kg)

## ▼ BarFly 100 System



**BAR-100G**  
BarFly 100 Fixture w/ Gel Frame and Louver 90°



**MTP-B41S**  
Mount w / Baby Short (16mm)



**BAL-107-G120**  
BarFly 100 Ballast, 120VAC

**BAL-107-G230**  
BarFly 100 Ballast, 230VAC

## ▼ Photometrics

BarFly 200	FC	344	96	43	25	16	11
	Feet	2	4	6	8	10	12
BarFly 100	FC	178	46	21	12	8	5
	Feet	2	4	6	8	10	12

BarFly 200	LUX	5297	1496	678	383	250	174
	Meters	0.5	1	1.5	2	2.5	3
BarFly 100	LUX	2659	743	338	191	125	87
	Meters	0.5	1	1.5	2	2.5	3

## ▼ Fixture Specifications

Fixture	Lamps	Lamp Type	Dimensions	Weight w/ Lamps
BarFly 200	2	F55/QFL	16.5 x 9 x 2.5" (41.5 x 22.5 x 6.5 cm)	4.9 lb (2.2 kg)
BarFly 100	1	F55/QFL	16 x 5.5 x 2.5" (40 x 14 x 6.5 cm)	3.2 lb (1.4 kg)

## ▼ Ballast Specifications

Ballast	Input Voltage	Output Frequency	Amps	Lamp Switch	Output Switch	Dimensions	Weight
BarFly 200	120VAC 50/60Hz	27KHz	2.1A	1- 2	HO/Std	9.5 x 9 x 2.5" (24 x 23 x 6.5 cm)	3.5 lb (1.6kg)
BarFly 200	230VAC 50/60Hz	27KHz	1.1A	1- 2	HO/Std	9.5 x 9.5 x 2.5" (24 x 24 x 6.5 cm)	4.0 lb (1.8kg)
BarFly 100	120VAC 50/60Hz	27KHz	1.1A	1- Off	HO/Std	11 x 2.5 x 2.5" (28 x 6.5 x 6.5 cm)	2 lb (0.9kg)
BarFly 100	230VAC 50/60Hz	27KHz	0.8A	1- Off	HO/Std	10.5 x 4 x 2.5" (26.5 x 10 x 6.5 cm)	2.8 lb (1.3kg)

## ▼ BarFly Accessories



**BAG-B1**  
Louver / Gel Bag



**BRD-BF1**  
BarFly 100 Snoot



**GFR-B1**  
BarFly 100 Gel Frame



**LVR-B145**  
BarFly 100 Louver 45°



**LVR-B245**  
BarFly 200 Louver 45°



**MTP-BFE**  
BarFly Edge Mount



**X09-G125**  
BarFly 100 Extension, 25ft



**X09-G225**  
BarFly 200 Extension, 25ft



**BAG-B21**  
Soft Bag BarFly 200/100 (1-Unit)




**KAS-B12**  
BarFly 100 Ship Case



**KAS-B22**  
BarFly 200 Ship Case



**KAS-QL6**  
6 Lamp (Quad) Carry Case



**55Q-K29**  
55W Kino KF29 Quad



**55Q-K55**  
55W Kino KF55 Quad