

Image DMX



Image 85 DMX



Image 45 DMX

The Image 85 DMX fixture's large soft light coverage and its small, energy footprint, combined with the ease of rigging compared to tungsten lighting sources makes it the darling of motion picture and television visual effects designers.

The relatively cool source takes about six different colored visual effects lighting colors, but most notably the specialized Kino Flo spiked blue and spiked green tubes for deep, rich saturation of color when lighting blue and green colored cyclorama stages.

Its smaller sibling, the Image 45 DMX, produces the same quality of light, with the same light control and beam spread features, but uses half the energy. The Image 45 works ideally on bluescreen and greenscreen stages that are no more than 15 feet in height.

Some key ingredients to both Image fixtures:

- DMX lamp switching
- HO/Standard switching
- Individual lamp control
- Gel Frame, Louver
- Instant-on, dead quiet
- True Match® daylight and tungsten balanced lamps

Available in Yoke Mount or Pole-Op.

▼ Image 85 DMX



IMG-85X-120
Image 85 DMX, 120VAC

IMG-85X-230
Image 85 DMX, 230VAC



IMG-85P-120
Image 85 DMX
Pole-Op, 120VAC

IMG-85P-230
Image 85 DMX
Pole-Op, 230VAC



GFR-180
Image 85 Gel Frame
(Included)



LVR-180S
Image 85 Louver/Silver
(Included)

▼ Image 45 DMX



IMG-45X-120
Image 45 DMX, 120VAC

IMG-45X-230
Image 45 DMX, 230VAC



IMG-45P-120
Image 45 DMX
Pole-Op, 120VAC

IMG-45P-230
Image 45 DMX
Pole-Op, 230VAC



GFR-140
Image 45 Gel Frame
(Included)



LVR-140S
Image 45 Louver/Silver
(Included)

▼ Image Accessories



BRD-180
Image 85 Barndoors

BRD-140
Image 45 Barndoors



DIM-5
Remote Lamp Selector



MTP-180
Junior Pin Assembly
for Yoke (28mm)



MTP-140
Baby Receiver Assembly
for Yoke (16mm)



KAS-140-1
Image 45 Ship Case



KAS-180-1
Image 85 Ship Case



KAS-180-2
Image 85 Ship Case
(2-Unit)



KAS-180-4
Image 85 Ship Case
(4-Unit)

▼ Photometrics

Image 85	FC	930	325	160	94	61	44	33	26	20	17
	Feet	2	4	6	8	10	12	14	16	18	20

Image 45	FC	531	173	84	49	32	22.5
	Feet	2	4	6	8	10	12

Image 85	LUX	12490	4748	2412	1443	958	678	505	394	320	265
	Meters	0.5	1	1.5	2	2.5	3	3.5	4	4.5	5

Image 45	LUX	7407	2261	1303	775	503	356
	Meters	0.5	1	1.5	2	2.5	3

▼ Fixture Specifications

Fixture	Input Voltage	Output Frequency	Amps	Switching	Lamp Type	Dimensions	Weight w/ Lamps
Image 85 DMX	120VAC 50/60Hz	25kHz	8.6A	1-8	F75/T12	54 x 28 x 6.5" (137 x 71 x 16.5cm)	38 lb (17.1kg)
Image 85 DMX	230VAC 50/60Hz	25kHz	4.3A	1-8	F75/T12	54 x 28 x 6.5" (137 x 71 x 16.5cm)	38 lb (17.1kg)
Image 45 DMX	120VAC 50/60Hz	25kHz	4.5A	1-4	F75/T12	54 x 17 x 6.5" (137 x 43 x 16.5cm)	25 lb (11.3kg)
Image 45 DMX	230VAC 50/60Hz	25kHz	2.3A	1-4	F75/T12	54 x 17 x 6.5" (137 x 43 x 16.5cm)	25 lb (11.3kg)

▼ Details



Pole-Operation



Image 85 fixtures, lighting translight on feature film set

▼ Image 85 DMX Kits



KIT-85-X1/120
Image 85 DMX Kit, 120VAC

KIT-85-X1/230
Image 85 DMX Kit, 230VAC

Contents
1 Image 85 DMX
1 Jr. Pin
1 Ship Case

Dimensions
56.5 x 8 x 35"
(143.5 x 20.5 x 89cm)
Weight
65 lb (29.3kg)



KIT-85-X2/120
Image 85 DMX Kit, 120VAC (2-Unit)

KIT-85-X2/230
Image 85 DMX Kit, 230VAC (2-Unit)

Contents
2 Image 85 DMX
2 Jr. Pin
1 Ship Case

Dimensions
56.5 x 16 x 35"
(143.5 x 40.5 x 89cm)
Weight
160 lb (72.5kg)



KIT-85-X4/120
Image 85 DMX Kit, 120VAC (4-Unit)

KIT-85-X4/230
Image 85 DMX Kit, 230VAC (4-Unit)

Contents
4 Image 85 DMX
4 Jr. Pin
1 Ship Case

Dimensions
35 x 33 x 64"
(89 x 84 x 162.5cm)
Weight
335 lb (152kg)

▼ Image 45 DMX Kit



KIT-45-X1/120
Image 45 DMX Kit, 120VAC

KIT-45-X1/230
Image 45 DMX Kit, 230VAC

Contents
1 Image 45 DMX
1 Jr. Pin
1 Ship Case

Dimensions
56.5 x 9 x 23.5"
(143.5 x 23 x 59.5cm)
Weight
48 lb (21.6kg)